

HS-25/25A Rocking Shaker

Shaker & Rocker

Introduction

The rocking shaker is a desktop oscillator that can be used directly in the greenhouse or in the incubator. It is widely used in the fixation of various electrophoresis gels, Coomassie blue staining, oscillating shaking during decolorization, silver nitrate staining Fix, dye, develop, etc.

Feature

- 1. Platform is made of stainless steel and natural rubber, which is acid & alkali resistant, non-deformation, easy-clean and spill-prevention.
- 2. Real-time display of speed and diminishing time.
- 3. The bearing is articulated rotating, secure and no wear,suitable for long time use.
- 4. Compact designed, save space.
- 5. Simple and beautiful appearance, humanization design.
- 6. Adopt stepper motor, low noise.

Accessories



Flat platform with non-slip rubber mat



Double deck flat platform with non-slip rubber mat



HS-25A

Parameter

Model	HS-25	HS-25A
Speed Range	5-80rpm	5-80rpm
Swing Cycloid	25mm (up and down) / 10°	25mm (up and down) / 10°
Time Range	1min-99h59min	1min-99h59min
Max. Load	5.0kgs (single-deck platform)	5.0kgs (double-deck platform)
Platform Dimension	L.280 x W.228mm	L.280 x W.228mm
Voltage	AC 100-230V, 50/60 Hz	AC 100-230V, 50/60 Hz
Power	50W	50W
Fuse	250V, 1A, Φ5x20	250V, 1A, Φ5x20
Dimension	W.284 x D.264 x H.134mm	W.284 x D.264 x H.248mm
Net Weight	5.2kgs	6.0kgs



HS-25